

**General Description**

The growth of fungus or algae embedded in the substrate is difficult to be removed. This product serves to exterminate those organisms that have high potential in causing defects in future.

**Features**

- Anti-bacteria up to 99%
- Fast killing active agent
- Water-based solution for easy handling
- Cover a wide spectrum of fungus & algae
- Easy application
- No damage of wall

**Recommended For**

- Interior or exteriors
  - Cement plaster surfaces
  - Concrete-related surfaces
  - Timber-related surfaces

**General Information**

Colour:	Milky white	Drying time: (at 25°C)	Touch dry : 30 mins
Type:	Dodecyl dimethyl benzyl ammonium chloride (non-mercurial)	Overcoat Time: (at 25°C)	24 hrs
Finishes:	N/A	Full Curing (at 25 °C)	N/A
Application Method:	Brush / Roller / Air-less spray	Specific Gravity: (at 25 °C)	0.96 ± 0.03
Theoretical Coverage:	14~18 m <sup>2</sup> /L/coat	Solid Content: (by volume)	<10%
Dilution:	No	Packing:	500mL / 20L
Dry Film Thickness:	N/A	Shelf Life:	36 months in sealed original packaging stored at room temperature and shaded place.

# **Nippon Paint Anti-Fungus Solution**

---

## **Surface Preparation**

- Cleaning surface by high pressure water jet, power brush, cloth or scraper to remove all unstable matter and organisms.
  - Apply Nippon Paint Anti-fungus solution with cloth, brush, roller or sprayer on mold directly from 30 cm distance. For mold on the ceiling, apply this agent on a cloth and remove them.
  - Wash surface with wet cloth to remove dead organism and residue of treatment solution after 10 mins.
  - Allow to dry before painting. For better performance, please use Nippon Paint Primer and Anti-Fungus Emulsion Paint afterwards.
- ◇ **Ensure fresh air ingress while applying and before dry done**
- ◇ **High humidity and cool temperature will result in longer drying time**

## **Limitations**

Avoid painting when the temperature is below 5°C or the humidity is over 85%. Do not paint when raining and rain is expected during painting or drying process.

## **Clean Up**

Wash tools with water immediately after use.

## **Safety Information**

Keep out of reach of children. If medical advice is needed, get the product container or label at hand for easy reference.

Be aware of sanding dust / spray mist. Protective gloves, eye or face protection are highly recommended. Keep away from sparks, heat, open flames and any other ignition sources.

Eating, drinking and smoking should be prohibited in areas where the material is handled, stored and processed.

In case of eye contact, rinse immediately with plenty of water. For splashed skin, clean thoroughly with soap and water. Seek medical attention if indication persists.

If you experience difficulties on breathing, leave applied area and obtain fresh air. If difficulties continue, immediately get medical attention.

Product must always be stored in a ventilated, cool and dry place.

Tightly close product container after each use.

## **Flash Point and Ignition Point**

Flash Point: N/A

Ignition Point: N/A

Note: The information given applies to the product and its performance under specific test condition. Due to the varied circumstances beyond our control under which the product may be applied, for specific applications, please contact Nippon Paint Project Sales Department. We reserve the right to modify our product specification without prior notice.

For further enquiries, please call:

**Nippon Paint (H.K.) Co., LTD**

Tel: (852) 2699 9333

Fax: (852) 2602 8844

Website: <http://www.nipponpaint.com.hk>