

General Description

This product is designed for removing of old emulsion paint film. It can penetrate into the paint layers, soften and break the bond between the paint and substrate. It is water-based, low odour, easy to apply and quick removal of old paint film which is an ideal choice for interior repainting.

Features

- Quick removal
- Ready for use
- Low Odour
- Eco-friendly

Recommended For

- Interior emulsion paint

General Information

Colour:	Milky white	Drying time: (at 25°C)	Touch dry : 15 mins
Type:	Propylene glycol butyl ether	Overcoat Time: (at 25°C)	N/A
Finishes:	N/A	Full Curing (at 25 °C)	N/A
Application Method:	Brush	Specific Gravity: (at 25 °C)	0.93 ± 0.03
Theoretical Coverage:	5 m ² /L/coat	Solid Content: (by volume)	<5%
Dilution:	No	Packing:	1L / 4L
Dry Film Thickness:	N/A	Shelf Life:	24 months in sealed original packaging stored at room temperature and shaded place.

Nippon Paint Super Paint Stripper

Surface Preparation

- Shake the product well until become milky.
- Apply by brush on the old paint film and ensure even coverage
- Leave for 15-20 minutes. Remove the soften coating with stripping knife before it dries out. Wait for 30 minutes for better result If apply on hard paint film. (The desired results may not be obtained if cannot remove the soften coating before it dries out)

❖ **Ensure fresh air ingress while applying and before dry done**

❖ **High humidity and cool temperature will result in longer drying time**

Limitations

Avoid painting when the temperature is below 5°C or the humidity is over 85%. Do not paint when raining and rain is expected during painting or drying process.

Clean Up

Wash tools with water immediately after use.

Safety Information

Keep out of reach of children. If medical advice is needed, get the product container or label at hand for easy reference.

Be aware of sanding dust / spray mist. Protective gloves, eye or face protection are highly recommended. Keep away from sparks, heat, open flames and any other ignition sources.

Eating, drinking and smoking should be prohibited in areas where the material is handled, stored and processed.

In case of eye contact, rinse immediately with plenty of water. For splashed skin, clean thoroughly with soap and water. Seek medical attention if indication persists.

If you experience difficulties on breathing, leave applied area and obtain fresh air. If difficulties continue, immediately get medical attention.

Product must always be stored in a ventilated, cool and dry place.

Tightly close product container after each use.

Flash Point and Ignition Point

Flash Point: N/A

Ignition Point: N/A

Note: The information given applies to the product and its performance under specific test condition. Due to the varied circumstances beyond our control under which the product may be applied, for specific applications, please contact Nippon Paint Project Sales Department. We reserve the right to modify our product specification without prior notice.

For further enquiries, please call:

Nippon Paint (H.K.) Co., LTD

Tel: (852) 2699 9333

Fax: (852) 2602 8844

Website: <http://www.nipponpaint.com.hk>