

General Description

Nippon Paint PYLOX Aerosol Spray Paint is a versatile product, it can be used anywhere on wood, metal, paper and other surfaces of interiors and exteriors. Application is quick and easy. A wide range of beautiful colours are available to meet the different needs of consumers.

Features

- Ozone-friendly;
- Eco-friendly and safe (CFC-free)
- Durable
- Washable
- Quick-drying
- Good adhesion
- Excellent color uniformity
- Wide selection of bright and attractive colours
- Easy application

Recommended For

- Interiors and exteriors
 - Cars / Vans / Lorries
 - Furniture / Tools
 - Railings / Grilles
 - Bicycles
 - Toys / Baskets
 - Doors / Windows
 - Cargo Packing
 - Photo frames
 - Office
 - Electrical appliances
 - Architectural models
 - Signage / Marking
 - Tire Rims
 - Motorcycles / Scooters
 - Helmets
 - Lighting fixtures

General Information

Colour:	Standard colours as per colour card	Drying time: (at 25°C)	Touch dry: 3-5 mins
Type:	Acrylic modified alkyd nitro-cellosolve paint	Overcoat Time: (at 25°C)	10 mins
Finishes:	Gloss & Matt for particular colors	Full Curing (at 25 °C)	7 days
Application Method:	Spray	Specific Gravity: (at 25 °C)	1.09-1.1
Theoretical Coverage:	Wood: 0.6~1.0 m ² per 400cc : 0.45-0.75 m ² per 300cc Metal : 0.8~1.6 m ² per 400cc : 0.6~1.2 m ² per 300cc	Solid Content: (by weight)	10-15%
Dilution:	N/A	Packing:	400cc per can 300cc per can (for pearl & fluorescents)
Dry Film Thickness:	20~30um	Shelf Life:	60 months in sealed original packaging stored at room temperature and shaded place.

Nippon Paint PYLOX Aerosol Spray Paint

Surface Preparation

All surfaces must be clean dry and free from dirt, grease and moisture, light sand is recommended to enhance adhesion.

Metal Surface: For new, unpainted metal surfaces, spray 3 passes of PYLOX Anti-Rust Primer followed by any PYLOX Spray Finish. If existing paint film is unstable, or if metal is corroded, scrape or sand vigorously until all loose matter and rust is removed.

Wood: For repainting, sand existing paint film and spray with any PYLOX Spray Finishes.

Application Details

Shake the can vigorously for at least 30 seconds after marble agitator in can rattles. Hold container approximately 30 cm from object to be sprayed. Press lever down with index finger, keeping the can in motion from side to side so that coating is deposited evenly. Several thin coats are better than one heavy coat. Each thin coat is dry for at least 10 minutes. Before storing leftover paint, ensure that the valve is not clogged by turning the can upside down and pushing spray head for approximately 1-3 seconds.

- ✧ **Ensure fresh air ingress while applying and before dry done**
- ✧ **High humidity and cool temperature will result in longer drying time**

Limitations

Avoid painting when the temperature is below 5°C or the humidity is over 85%. Do not paint when raining and rain is expected during painting or drying process.

Safety Information

Keep out of reach of children. If medical advice is needed, get the product container or label at hand for easy reference.

Be aware of sanding dust / spray mist. Protective gloves, eye or face protection are highly recommended. Keep away from sparks, heat, open flames and any other ignition sources.

Eating, drinking and smoking should be prohibited in areas where the material is handled, stored and processed.

In case of eye contact, rinse immediately with plenty of water. For splashed skin, clean thoroughly with soap and water. Seek medical attention if indication persists.

If you experience difficulties on breathing, leave applied area and obtain fresh air. If difficulties continue, immediately get medical attention.

Product must always be stored in a ventilated, cool and dry place.

Tightly close product after each use.

Flash Point and Ignition Point

Flash Point: 22~25.6°C

Ignition Point: N/A

Note: The information given applies to the product and its performance under specific test condition. Due to the varied circumstances beyond our control under which the product may be applied, for specific applications, please contact Nippon Paint Project Sales Department. We reserve the right to modify our product specification without prior notice.

For further enquiries, please call:

Nippon Paint (H.K.) Co., LTD

Tel: (852) 2699 9333

Fax: (852) 2602 8844

Website: <http://www.nipponpaint.com.hk>