

General Description

Nippon Paint Wall mold warrior waterproof spray is made of Nano fluorine from Japan, its waterproof capability is much better than that of other silicone based waterproof spray. It can also permeate into the wall to prevent moisture by crystallization. Therefore, It is much effective than other coating products.

Features

- Penetrating wall efficiently, preventing wall mold sustainably and curing wall cancer efficiently.
- Neutral pH
- Non-clogging , more durable nozzle head design.
- Easy, fast, and convenient to use.
- Non film, remain unchanged for original texture of substrate
-

Recommended For

- Outdoor Wood,
- Bricks
- Tile,
- Stone,
- Architectural concrete
- cement
- Gypsum board
- Ceiling

Certification(s)



General Information

Colour:	Transparent	Drying time: (at 25~30℃)	Surface dry: 30 mins Hard dry: 24 hours
Type	Fluoridated Resin	Overcoat Time: (at 25~30℃)	30 ~ 40 mins
Finishes:	N/A	Full Curing (at 25 ℃)	24 hours
Application Method:	Spray	Specific Gravity: (at 25 ℃)	0.81 (with gas)
Theoretical Coverage:	3.305 -6.61 m ² /300ml/coat	Solid Content: (by weight)	2% (without gas)
Dilution:	N/A	Packing:	300 ml
Dry Film Thickness:	5-15μm	Shelf Life:	5 years

Nippon Paint Wall Mold Warrior Waterproof Spray

Surface Preparation

All surfaces must be clean, dry and free from oil, grease, dirt, contaminants and loose materials. If wall cancer is appeared on the surface, it must be cleaned with iron brush or sand paper.

- ✧ **Ensure fresh air ingress while applying and before dry done**
- ✧ **High humidity and cool temperature will result in longer drying time**

Application Details

- For the application of interior wall, the application area needs to be slightly larger than the area of wall cancer in order to cover all affected area. Application for two times is recommended
- For the application of exterior wall, the application area should also be increased. Apply one to two times for filling the small pores of the wall in order to achieve the best sealing and waterproof performance.

Limitations

Avoid painting when the temperature is below 5°C or the humidity is over 85%. Do not paint when raining and rain is expected during painting or drying process.

Clean Up

Wash painting tools with water immediately after use.

Safety Information

Keep out of reach of children. If medical advice is needed, get the product container or label at hand for easy reference.

Be aware of sanding dust / spray mist. Protective gloves, eye or face protection are highly recommended. Keep away from sparks, heat, open flames and any other ignition sources.

Eating, drinking and smoking should be prohibited in areas where the material is handled, stored and processed.

In case of eye contact, rinse immediately with plenty of water. For splashed skin, clean thoroughly with soap and water. Seek medical attention if indication persists.

If you experience difficulties on breathing, leave applied area and obtain fresh air. If difficulties continue, immediately get medical attention.

Product must always be stored in a ventilated, cool and dry place.

Tightly close product container after each use.

Flash Point and Ignition Point

Flash Point: 45.6°C

Ignition Point: 210°C

Note: The information given applies to the product and its performance under specific test condition. Due to the varied circumstances beyond our control under which the product may be applied, for specific applications, please contact Nippon Paint Project Sales Department. We reserve the right to modify our product specification without prior notice.

For further enquiries, please call:

Nippon Paint (H.K.) Co., LTD

Tel: (852) 2699 9333

Fax: (852) 2602 8844

Website: <http://www.nipponpaint.com.hk>